



16' TANDEM AXLE UTILITY TRAILER 2' DOVE TAIL WITH FOLD-IN GATE/RAMP



SPECIFICATIONS

Length :	16 ft. (4.87 m.)
Width :	83 in. (2.10 m.)
GVWR :	7,000 lbs. (3,175 kgs.)
GAWR :	3,500 lbs. (1,588 kgs.)
Weight :	1,800 lbs. (816 kgs.)
Payload Cap. :	5,200 lbs. (2,358 kgs.)
Axle Type :	2 x 3,500 lbs. (1,588 kgs.)
Brake Type :	Electric
Suspension :	4-Leaf Springs
Tires :	ST205 15 in. Tire and Rims
Coupler Type :	Bumperpull
Coupler Spec. :	2 in. A-Frame Coupler with Safety Chains
Jack :	5,000 lbs. Rated Top Wind Jack
Deck :	Treated Wood
Deck Height :	20 in. (0.5 m.)
Ramp/Gate :	Fold-In Rear Ramp Gate

PREMIUM FEATURES

Fold-in gate/ramp
2' Dove tail
Removable side load ramps, slip resistant
Steel Fenders with Side Steps
Powder coated Black and Galvanized Finish
Available.

Available models:

*Powder coated black: **TNUL21632ESYKA***

*Galvanized : **TNUL21632ESYGA***